HP/kW	• 115 / 86
Engine type	<ul><li>8-valve single overhead cam (SOHC)</li><li>Inline 4</li></ul>
Displacement (L)	• 2.1
Full throttle RPM	• 5300-6300
Air induction	Performance-Tuned Scroll Intake Manifold
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel
Alternator amp / Watt	• 35 amp / 441 watt with water-cooled voltage regulator
Recommended fuel	• Unleaded Regular 87 Octane Minimum (R+M/2) or 90
Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	• Yes
Starting	<ul><li> Electric (turn-key)</li><li> Smart Start Electric</li></ul>
Controls	Mechanical throttle & shift
Steering	<ul><li>Big Tiller Compatible</li><li>Dual cable mechanical</li><li>Hydraulic power steering</li></ul>
Shaft length	• 20" / 508 mm • 25" / 635 mm
Gearcase ratio	• 2.07:1
Dry weight *Lightest model	• 359 lbs / 163 kg
Bore and stroke	• 3.5 x 3.2 /90 x 81
Ignition	SmartCraft ECM 07 Digital Inductive
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	• F-N-R
Gearcase options	• Standard
Trim system	<ul><li>Power Tilt</li><li>Power Trim</li></ul>
Exhaust system	Through prop
Color	Phantom Black
Lubrication system	• Wet sump
Oil Capacity	• 5.5 qts / 5.2 1
Maximum Trim Range	• 22° (-6° to 16°)
Maximum Tilt Range	• 70° (-6° to 64°)