HP/kW	• 15 / 11.1
Engine type	• Inline 2
Displacement (CID/CC)	• 20.3 / 333
Full throttle RPM	• 5700 - 6200
Fuel induction system	• 2 valves per cylinder, single overhead cam
Alternator amp / Watt	• 12/145 electric
Recommended fuel	• 87 octane compatible (up to 10% ethanol)
Recommended oil	25W-40 Synthetic BlendMercury FC-W 10W-30 4-Stroke Marine Oil
Engine protection operator warning system	Low oil pressureOver-revOverheatSensor failure
Starting	ElectricManual
Steering	RemoteTiller
Shaft length	• 15" / 381 mm • 20" / 508 mm
Gearcase ratio	• 2.15:1
Dry weight *Lightest model	• 99 lbs / 45 kg
CARB star rating	• 3
Bore and stroke	• 2.40 x 2.24" / 61 x 57 mm
Ignition	CDI w/electronic spark advance
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	• F-N-R
Gearcase options	Standard
Trim system	ManualPower Tilt
Trim positions	• 6
Exhaust system	Through prop
Shallow water drive	• Yes
Shallow water trim range (degrees)	• 16
Remote fuel tank (optional)	• Yes
Remote fuel tank standard (gal / L)	• 6.6 / 25
Color	Phantom Black