HP/kW	• 30 / 22.4
Engine type	• Inline 3
Displacement (CID/CC)	• 32.1 / 526
Full throttle RPM	• 5250-6250
Fuel induction system	• 2 valves per cylinder, single overhead cam
Alternator amp / Watt	• 15 amp / 186 watt
Recommended fuel	• 87% octane / up to 10% ethanol
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	Low oil pressureOver-revOverheatSensor failure
Starting	Electric (turn-key)Manual
Steering	RemoteTiller
Shaft length	• 15" / 381 mm • 20" / 508 mm
Gearcase ratio	• 1.92:1
Dry weight *Lightest model	• 172 lbs / 78 kg
CARB star rating	• 3
Bore and stroke	• 2.40 x 2.36" / 61 x 60 mm
Ignition	CDI w/electronic spark advance
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	• F-N-R
Gearcase options	Standard
Trim system	 Gas assist Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	• 16
Remote fuel tank standard (gal / L)	• 6.6 / 25
Color	Phantom Black