

HP / kW	<ul style="list-style-type: none"> • 150 / 110
Engine type	<ul style="list-style-type: none"> • 8-valve single overhead cam (SOHC) • Inline 4
Displacement (L)	<ul style="list-style-type: none"> • 3.0
Full throttle RPM	<ul style="list-style-type: none"> • 5000-5800
Air induction	<ul style="list-style-type: none"> • Performance-Tuned Scroll Intake Manifold
Fuel induction system	<ul style="list-style-type: none"> • Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	<ul style="list-style-type: none"> • 60 amp / 756 watt (Belt-Driven)
Recommended fuel	<ul style="list-style-type: none"> • Unleaded Regular 87 Octane Minimum (R+M/2) or 90 Octane Minimum
Recommended oil	<ul style="list-style-type: none"> • Mercury FourStroke Oil 10W-30
Engine protection operator	<ul style="list-style-type: none"> • SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	<ul style="list-style-type: none"> • Yes
Starting	<ul style="list-style-type: none"> • Electric (turn-key) • Smart Start Electric
Controls	<ul style="list-style-type: none"> • Mechanical throttle & shift
Steering	<ul style="list-style-type: none"> • Big Tiller Compatible • Dual cable mechanical • Electro-Hydraulic Power Steering Optional on Duals • Hydraulic power steering
Shaft length	<ul style="list-style-type: none"> • 20" / 508 mm • 25" / 635 mm
Gearcase ratio	<ul style="list-style-type: none"> • 1.92:1
Dry weight *Lightest model	<ul style="list-style-type: none"> • 455 lbs / 206 kg
CARB star rating	<ul style="list-style-type: none"> • 3
Bore and stroke	<ul style="list-style-type: none"> • 4.0 x 3.6" / 102 x 92 mm
Ignition	<ul style="list-style-type: none"> • SmartCraft ECM 70 Digital Inductive
Fuel system	<ul style="list-style-type: none"> • Electronic Fuel Injection (EFI)
Cooling system	<ul style="list-style-type: none"> • Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none"> • F-N-R
Gearcase options	<ul style="list-style-type: none"> • Standard
Trim system	<ul style="list-style-type: none"> • Power Tilt • Power Trim
Exhaust system	<ul style="list-style-type: none"> • Through prop
Counter Rotation	<ul style="list-style-type: none"> • Available
Color	<ul style="list-style-type: none"> • Phantom Black
Lubrication system	<ul style="list-style-type: none"> • Wet sump
Oil Capacity	<ul style="list-style-type: none"> • 6.3 qts / 6.0l

Maximum Trim Range	• 22° (-6° to 16°)
Maximum Tilt Range	• 73° (-6° to 67°)