HP/kW	• 175 / 130
Engine type	• V-6
MidSection	Conventional MidSection
Displacement (CID/CC)	• 209 CID
Displacement (L)	• 3.4L
Cylinder Configuration	V-6 [64 degree] with Dual Overhead Cam [DOHC] and
Full throttle RPM	• 5000-5800
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled
Alternator amp / Watt	• 85-amp (1071 Watt) with Idle Charge
Recommended fuel	• Unleaded Regular 87 Octane Minimum (R+M/2) or 90
Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator	SmartCraft Engine Guardian
Compatible with SmartCraft digital	• Yes
Starting	Electric Start with SmartStart Protection
Controls	Remote Mechanical or Digital Throttle & Shift (DTS)
Steering	<ul><li>Big Tiller (optional)</li><li>Hydraulic (standard)</li><li>Power (optional)</li></ul>
Shaft length	• 20" / 508 mm • 25" / 635 mm
Gearcase ratio	• 1.85:1
Dry weight *Lightest model	• 475 lbs / 216 kgs
CARB star rating	• 3
Bore and stroke	• 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	SmartCraft PCM 112 Digital Inductive
Cooling system	Water-cooled with thermostat
Gear shift	• F-N-R
Gearcase options	• 4.8"
Trim system	Power trim and tilt
Exhaust system	Through prop
Color	Phantom Black
Lubrication system	Integrated wet sump
Oil Capacity	• 7.0 Quarts / 6.6 Liters
<b>Maximum Trim Range</b>	• 20° (-6° to 14°)

**Maximum Tilt Range** 

• 73° (-6° to 67°)