

HP / kW	<ul style="list-style-type: none"> • 75 / 56
Engine type	<ul style="list-style-type: none"> • 8-valve single overhead cam (SOHC) • Inline 4
Displacement (L)	<ul style="list-style-type: none"> • 2.1
Full throttle RPM	<ul style="list-style-type: none"> • 4500-5500
Air induction	<ul style="list-style-type: none"> • Performance-Tuned Scroll Intake Manifold
Fuel induction system	<ul style="list-style-type: none"> • Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	<ul style="list-style-type: none"> • 35 amp / 441 watt with water-cooled voltage regulator
Recommended fuel	<ul style="list-style-type: none"> • Unleaded Regular 87 Octane Minimum (R+M/2) or 90 Octane Minimum
Recommended oil	<ul style="list-style-type: none"> • Mercury FourStroke Oil 10W-30
Engine protection operator	<ul style="list-style-type: none"> • SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	<ul style="list-style-type: none"> • Yes
Starting	<ul style="list-style-type: none"> • Smart Start Electric
Controls	<ul style="list-style-type: none"> • Mechanical throttle & shift
Steering	<ul style="list-style-type: none"> • Big Tiller Compatible • Dual cable mechanical • Hydraulic power steering
Shaft length	<ul style="list-style-type: none"> • 20" / 508 mm
Gearcase ratio	<ul style="list-style-type: none"> • 2.07:1
Dry weight *Lightest model	<ul style="list-style-type: none"> • 359 lbs / 163 kg
CARB star rating	<ul style="list-style-type: none"> • 3
Bore and stroke	<ul style="list-style-type: none"> • 3.5 x 3.2" / 90 x 81 mm
Ignition	<ul style="list-style-type: none"> • SmartCraft ECM 70 Digital Inductive
Fuel system	<ul style="list-style-type: none"> • Electronic Fuel Injection (EFI)
Cooling system	<ul style="list-style-type: none"> • Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none"> • F-N-R
Gearcase options	<ul style="list-style-type: none"> • Standard
Trim system	<ul style="list-style-type: none"> • Power Tilt • Power Trim
Exhaust system	<ul style="list-style-type: none"> • Through prop
Shallow water trim range	<ul style="list-style-type: none"> • 20
Color	<ul style="list-style-type: none"> • Phantom Black
Lubrication system	<ul style="list-style-type: none"> • Wet sump
Oil Capacity	<ul style="list-style-type: none"> • 5.5 qts / 5.2 l
Maximum Trim Range	<ul style="list-style-type: none"> • 22° (-6° to 16°)
Maximum Tilt Range	<ul style="list-style-type: none"> • 70° (-6° to 64°)