| HP/kW | • 90 / 67 | | | |
|---|--|--|--|--|
| Engine type | • 8-valve single overhead cam (SOHC) | | | |
| 0 02 | • Inline 4 | | | |
| Displacement (L) | • 2.1 | | | |
| Full throttle RPM | • 5000-6000 | | | |
| Air induction | Performance-Tuned Scroll Intake Manifold | | | |
| Fuel induction system | Computer Controlled Multi-Port Electronic Fuel | | | |
| Alternator amp / Watt | • 35 amp / 441 watt with water-cooled voltage regulator | | | |
| Recommended fuel | • Unleaded Regular 87 Octane Minimum (R+M/2) or 90 | | | |
| Recommended oil | Mercury FourStroke Oil 10W-30 | | | |
| Engine protection operator | SmartCraft Engine Guardian | | | |
| Compatible with SmartCraft digital technology | • Yes | | | |
| Starting | Smart Start Electric | | | |
| Controls | Mechanical throttle & shift | | | |
| Steering | Big Tiller CompatibleDual cable mechanicalHydraulic power steering | | | |
| Shaft length | • 20" / 508 mm • 25" / 635 mm | | | |
| Gearcase ratio | • 2.07:1 or 2.38:1 (CT model) | | | |
| Dry weight *Lightest model | • 359 lbs / 163 kg; 363 lbs / 165 kg (CT model) | | | |
| CARB star rating | • 3 | | | |
| Bore and stroke | • 3.5 x 3.2" / 90 x 81 mm | | | |
| Ignition | SmartCraft ECM 70 Digital Inductive | | | |
| Fuel system | • Electronic Fuel Injection (EFI) | | | |
| Cooling system | Water-cooled with thermostat | | | |
| Gear shift | • F-N-R | | | |
| Gearcase options | Command ThrustStandard | | | |
| Trim system | Power TiltPower Trim | | | |
| Exhaust system | Through prop | | | |
| Shallow water trim range | • 20 | | | |
| Color | Phantom Black | | | |
| Lubrication system | • Wet sump | | | |
| Oil Capacity | • 5.5 qts / 5.2 1 | | | |
| On Capacity | • 5.5 qts / 5.2 l | | | |
| Maximum Trim Range | 5.5 qts / 5.2 l 22° (-6° to 16°) | | | |