

HP / kW	<ul style="list-style-type: none"> • 225 / 168
Engine type	<ul style="list-style-type: none"> • V-6
MidSection	<ul style="list-style-type: none"> • Conventional MidSection
Displacement (CID/CC)	<ul style="list-style-type: none"> • 209 CID
Displacement (L)	<ul style="list-style-type: none"> • 3.4L
Cylinder Configuration	<ul style="list-style-type: none"> • V-6 [64 degree] with Dual Overhead Cam [DOHC] and
Full throttle RPM	<ul style="list-style-type: none"> • 5200-6000
Air induction	<ul style="list-style-type: none"> • Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	<ul style="list-style-type: none"> • Electronic Fuel Injection (EFI) Computer Controlled
Alternator amp / Watt	<ul style="list-style-type: none"> • 85-amp (1071 Watt) with Idle Charge
Recommended fuel	<ul style="list-style-type: none"> • Unleaded Regular 87 Octane Minimum (R+M/2) or 90
Recommended oil	<ul style="list-style-type: none"> • NMMA Certified FCW SAE 10W-30
Engine protection operator	<ul style="list-style-type: none"> • SmartCraft Engine Guardian
Compatible with SmartCraft digital	<ul style="list-style-type: none"> • Yes
Starting	<ul style="list-style-type: none"> • Electric Start with SmartStart Protection
Controls	<ul style="list-style-type: none"> • Remote Mechanical or Digital Throttle & Shift (DTS)
Steering	<ul style="list-style-type: none"> • Big Tiller (optional) • Hydraulic (standard) • Power (optional)
Shaft length	<ul style="list-style-type: none"> • 20" / 508 mm • 25" / 635 mm • 30" / 762 mm
Gearcase ratio	<ul style="list-style-type: none"> • 1.85:1
Dry weight *Lightest model	<ul style="list-style-type: none"> • 475 lbs / 216 kgs
CARB star rating	<ul style="list-style-type: none"> • 3
Bore and stroke	<ul style="list-style-type: none"> • 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	<ul style="list-style-type: none"> • SmartCraft PCM 112 Digital Inductive
Cooling system	<ul style="list-style-type: none"> • Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none"> • F-N-R
Gearcase options	<ul style="list-style-type: none"> • 4.8"
Trim system	<ul style="list-style-type: none"> • Power trim and tilt
Exhaust system	<ul style="list-style-type: none"> • Through prop
Counter Rotation	<ul style="list-style-type: none"> • Available

Color	<ul style="list-style-type: none"> • Cold Fusion White • Pearl Fusion White • Phantom Black • Warm Fusion White
Lubrication system	<ul style="list-style-type: none"> • Integrated wet sump
Oil Capacity	<ul style="list-style-type: none"> • 7.0 Quarts / 6.6 Liters
Maximum Trim Range	<ul style="list-style-type: none"> • 20° (-6° to 14°)
Maximum Tilt Range	<ul style="list-style-type: none"> • 73° (-6° to 67°)