



HP / kW	<ul style="list-style-type: none"> • 300 / 224
Engine type	<ul style="list-style-type: none"> • V-8
MidSection	<ul style="list-style-type: none"> • Advanced MidSection (AMS)
Displacement (CID/CC)	<ul style="list-style-type: none"> • 279 CID
Displacement (L)	<ul style="list-style-type: none"> • 4.6L
Cylinder Configuration	<ul style="list-style-type: none"> • V-8 [64 degree] with Dual Overhead Cam [DOHC] and
Full throttle RPM	<ul style="list-style-type: none"> • 5200-6000
Air induction	<ul style="list-style-type: none"> • Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	<ul style="list-style-type: none"> • Electronic Fuel Injection (EFI) Computer Controlled
Alternator amp / Watt	<ul style="list-style-type: none"> • 115-amp (1449 Watt) with Idle Charge
Recommended fuel	<ul style="list-style-type: none"> • Unleaded Regular 87 Octane Minimum (R+M/2) or 90

Recommended oil	<ul style="list-style-type: none"> • NMMA Certified FCW SAE 10W-30
Engine protection operator	<ul style="list-style-type: none"> • SmartCraft Engine Guardian
Compatible with SmartCraft digital	<ul style="list-style-type: none"> • Yes
Starting	<ul style="list-style-type: none"> • Electric Start with SmartStart Protection
Controls	<ul style="list-style-type: none"> • Digital Throttle & Shift (DTS)
Steering	<ul style="list-style-type: none"> • Electro-hydraulic power steering • Joystick Piloting for Outboards
Shaft length	<ul style="list-style-type: none"> • 20" / 508 mm • 25" / 635 mm • 30" / 762 mm
Gearcase ratio	<ul style="list-style-type: none"> • 1.75:1 or 1.85:1
Dry weight *Lightest model	<ul style="list-style-type: none"> • 600 lbs / 272 kgs
CARB star rating	<ul style="list-style-type: none"> • 3
Bore and stroke	<ul style="list-style-type: none"> • 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	<ul style="list-style-type: none"> • SmartCraft PCM 112 Digital Inductive
Cooling system	<ul style="list-style-type: none"> • Water-cooled with thermostat
Gear shift	<ul style="list-style-type: none"> • F-N-R
Gearcase options	<ul style="list-style-type: none"> • 5.44"
Trim system	<ul style="list-style-type: none"> • Power trim and tilt
Exhaust system	<ul style="list-style-type: none"> • Through prop
Counter Rotation	<ul style="list-style-type: none"> • Available
Color	<ul style="list-style-type: none"> • Cold Fusion White • Pearl Fusion White • Phantom Black • Warm Fusion White
Lubrication system	<ul style="list-style-type: none"> • Integrated wet sump
Oil Capacity	<ul style="list-style-type: none"> • 7.0 Quarts / 6.6 Liters
Maximum Trim Range	<ul style="list-style-type: none"> • 20° (-6° to 14°)
Maximum Tilt Range	<ul style="list-style-type: none"> • 73° (-6° to 67°)