HP/kW	• 60 / 45
Engine type	• Inline 4
Displacement (CID/CC)	• 60.8 / 995
Full throttle RPM	• 5500-6000
Fuel induction system	• 2 valves per cylinder, single overhead cam
Alternator amp / Watt	• 18 amp / 226 watt
Recommended fuel	• 87% octane / up to 10% ethanol
Recommended oil	Mercury FourStroke 25W40 Marine Oil
Engine protection operator warning	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	• Yes
Starting	Electric (turn-key)
Steering	<ul><li>Remote</li><li>Tiller</li></ul>
Shaft length	• 20" / 508 mm • 25" / 635 mm (CT model)
Gearcase ratio	• 1.83:1 or 2.33:1 (CT model)
Dry weight *Lightest model available	• 247 lbs / 112 kg
CARB star rating	• 3
Bore and stroke	• 2.56 x 2.95" / 65 x 75 mm
Ignition	<ul><li>ECM 07 Digital Inductive (CT model)</li><li>ECM 70</li></ul>
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	• F-N-R
Gearcase options	<ul><li>Command Thrust (CT)</li><li>Standard</li></ul>
Trim system	Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	• 20
Remote fuel tank (optional)	• Yes
Color	Phantom Black
Lubrication system	Wet sump