

HP / kW	<ul style="list-style-type: none"> • 60 / 45
Engine type	<ul style="list-style-type: none"> • 8-valve single overhead cam (SOHC) • Inline 4
Displacement (CID/CC)	<ul style="list-style-type: none"> • 60.8 / 995
Full throttle RPM	<ul style="list-style-type: none"> • 4500-5500
Air induction	<ul style="list-style-type: none"> • Performance-Tuned Scroll Intake Manifold
Fuel induction system	<ul style="list-style-type: none"> • Computer Controlled Multi-Port Electronic Fuel Injection
Alternator amp / Watt	<ul style="list-style-type: none"> • 18 amp / 226 watt
Recommended fuel	<ul style="list-style-type: none"> • Unleaded Regular 87 Octane Minimum (R+M/2) or 90
Recommended oil	<ul style="list-style-type: none"> • NMMA Certified FCW SAE 25W-40
Engine protection operator warning system	<ul style="list-style-type: none"> • SmartCraft Engine Guardian
Starting	<ul style="list-style-type: none"> • Electric (turn-key)
Controls	<ul style="list-style-type: none"> • Mechanical throttle & shift
Steering	<ul style="list-style-type: none"> • Big Tiller • Remote
Shaft length	<ul style="list-style-type: none"> • 20" / 508 mm • 22.5" / 572 mm • 25" / 635 mm
Gearcase ratio	<ul style="list-style-type: none"> • 2.33:1
Dry weight *Lightest model	<ul style="list-style-type: none"> • 260 lbs / 118 kg
Bore and stroke	<ul style="list-style-type: none"> • 2.56 x 2.95" / 65 x 75 mm
Ignition	<ul style="list-style-type: none"> • SmartCraft ECM 07 Digital Inductive
Cooling system	<ul style="list-style-type: none"> • Water-cooled with thermostat
Gearcase options	<ul style="list-style-type: none"> • Command Thrust
Trim system	<ul style="list-style-type: none"> • Gas Assist available • Power Tilt • Power Trim
Exhaust system	<ul style="list-style-type: none"> • Through prop
Lubrication system	<ul style="list-style-type: none"> • Wet sump
Oil Capacity	<ul style="list-style-type: none"> • 3.0 qts / 2.8 l